W8 - 14A
48" x 48"

W8 - 14
48" x 48"

W8 - 8a
48" x 48"

W20 - 7a (S)
48" x 48"



R2 - 5a
30" x 48"
R2 - 5a (S)
48" x 60"

R4 - 1
24" x 30"

G20 - 1
60" x 36"

W8 - 10
48"x48"

W8 - 10(S)
48"x48"

W8-3(MOD)
48"x48"

W20 - 4
48" x 48"

W20 - 2
48" x 48"



(L OR R)
W1-8
48" x 24"

W1-8 (S)
60" x 30"

W8-3
48" x 48"



R2 - 1
30" x 48"
R2 - 1 (S)
48" x 60"

24" x 24"
30" x 30" (S)

M4-11
30"x24"
M4-11 (S)
48"x36"

W20 - 3
48" x 48"

W20 - 1
48" x 48"

(L OR R)
W4-2 (S)
48" x 48"

(L OR R)
W1-4 (S)
48" x 48"

M4-9X
30"x24"
M4-9X (S)
48"x36"

24" x 24"
30" x 30" (S)

W13 - 1
18" x 18"
W13 - 1 (S)
24" x 24"

M4-8N
36" x 12" MIN.
(SIZE WILL VARY WITH LENGTH OF STREET NAME)

STREET NAME SIGN TO BE USED IN CONJUNCTION WITH M4 - 9 SIGNS BLACK ON ORANGE

W21 - 6 (S)
48" x 48"

(L OR R)
(CENTER)
W20 - 5
48" x 48"

W20 - 2
48" x 48"

NOTE: THE BORDER, THE WORDS "GIVE US A", "SLOW DOWN", AND THE BRAKE PEDAL ARE BLACK; LEAVING THE WORD "BRAKE" ORANGE.

W8 - 1
48" x 48"

M4-9L (LEFT)
M4-9R (RIGHT)
30"x24"
M4-9 (L or R) (S)
48"x36"

M4-9LX (LEFT)
M4-9RX (RIGHT)
30"x24"
M4-9 (L OR R) S
48"x36"

R11 - 2
48" x 30"



R11 - 4
60" x 30"

R11 - 3
60" x 30"



G20 - 2
60" x 24"

M4-10L (LEFT)
M4-10R (RIGHT)
48" x 15"

General Notes For Signs

1) INSTALLATION , DIMENSIONS, COLORS, AND DETAILS OF VARIOUS SIZED SIGNS, AND ACCESSORY PANELS TO FOLLOW STANDARDS IN THE CURRENT "STANDARD HIGHWAY SIGN PUBLICATION" AND THE CURRENT "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS".

2) (S) REPSENTS A SPECIAL SIZED SIGN

3) LETTERS AND NUMBERS SHALL CONFORM TO THE CURRENT MANUAL, "STANDARD ALPHABETS FOR HIGHWAY SIGNS" U.S. DEPT. OF TRANSPORTATION, FEDERAL HIGHWAY ADMINISTRATION.

4) THE CONTRACTOR SHALL OBTAIN THE APPROVAL OF THE ENGINEER FOR THE DISTANCE TO BE USED ON THE ADVANCE WARNING SIGNS, AND FOR THE SPEED LIMIT TO BE USED ON THE R2-1 SIGN.

DISTANCE LEGEND
SIGN NUMBER FOLLOWED BY

LETTER	DISTANCE
A	1000'
B	1500'
C	500'
D	_MILE
E	_MILES AHEAD
F	AHEAD

BACKING MATERIAL

1) ALUMINUM SHALL BE FLAT SHEET OF 6061-T6 ALLOY, .100" GAUGE

Temporary Sign Supports

1) SIGN SUPPORTS SHALL BE OF WELL SEASONED LUMBER, S4S, FREE OF SPLITS, KNOTS, WARPS, OR OF STEEL OR ALUMINUM COMPONENTS.

2) WOOD POSTS SHALL HAVE A UNIFORM CROSS-SECTION AND SHALL NOT EXCEED THE FOLLOWING DIMENSIONS FOR:

SINGLE POST:	4"X6"
	3"X8" OR
TWO POSTS:	4"X6"
	3"X8" OR
THREE POSTS:	4"X6"

3) NO BRACING IS PERMITTED. VERTICAL CLEARANCES FOR SIGNS MOUNTED ON WOOD SUPPORTS SHALL BE 7' DESIRABLE, 6' MIN. EMBEDMENT DEPTH FOR THE WOOD POST SHALL NOT EXCEED 3.5'.

4) STEEL OR ALUMINUM POSTS SHALL BE IN ACCORDANCE WITH THE STANDARD DETAIL FOR "SELECTIVE DIRECTIONAL SIGNS, CONSTRUCTION AND 'M', 'W' AND 'R' SENDAWAY SIGN SUPPORTS".

5) TEMPORARY SIGN SUPPORTS NOT MEETING THIS CRITERIA SHALL BE SHIELDED BY A LONGITUDINAL BARRIER OR CRASH CUSHION.

SIGN FACES

1) SIGN FACES SHALL BE REFLECTIVE SHEETING, TYPE 11

FASTENING

1) ALL SIGNS SHALL BE SECURELY FASTENED TO THEIR SUPPORTS WITH BOLTS, NUTS AND WASHERS OF ALUMINUM (2024-T4 ALLOY) OR HOT-DIP GALVANIZED STEEL (A.S.T.M. 169)

COPYRIGHT 2008, T&M ASSOCIATES — ALL RIGHTS RESERVED.
THE COPYING OR REUSE OF THIS DOCUMENT, OR PORTIONS THEREOF, FOR OTHER THAN THE ORIGINAL PROJECT OR THE PURPOSE ORIGINALLY INTENDED, WITHOUT THE WRITTEN PERMISSION OF T&M ASSOCIATES, IS PROHIBITED.

City of Jersey City
Division of Engineering
575 ROUTE 440
JERSEY CITY, NEW JERSEY 07305
(201) 547-4412

NO.	REVISIONS	DATE
1	Raised Manholes Sign Added	7/09

CITY OF JERSEY CITY
STANDARDS

NO.	REVISIONS	DATE

William R. Goble, P.E.
Director
Division of Engineering
NJ P.E. Lic. No. 24798

Date

Construction Signs

DRAWN BY	DESIGNED BY	CHECKED BY
PROJECT NO.	CADD FILE	SCALE

DRAWING
SHEET
13
17